



THERMOCOUPLES

Catalog Number	Description	Temperature Range	Weight (kgs)
104A TC105	.32cm diameter x 15.2cm long stainless-steel probe. 122cm long, fiberglass insulated duplex lead with stainless steel overbraid. With miniature plug. For liquid immersion. Type J.	0-370C	.2
104A TC105K	.32cm diameter x 15.2cm long stainless-steel probe. 122cm long, fiberglass insulated duplex lead with stainless steel overbraid. With miniature plug. For liquid immersion. Type K.	95-1260C	.2
104A TC105T	.32cm diameter x 15.2cm long stainless-steel probe. 122cm long, fiberglass insulated duplex lead with stainless steel overbraid. With miniature plug. For liquid immersion. Type T.	-200 – 350C	.2
104A TC110	.32cm diameter x 15.2 long PTFE coated stainless-steel probe. 122cm long, PTFE insulated duplex lead. With miniature plug. For liquid immersion.	0-260C	.2
104A TC115	183cm long, fiberglass-insulated duplex lead wire with 20-gauge welded tip. With miniature plug. Not for liquid immersion.	0-480C	.3
104A TC120	91.4cm long, fiberglass-insulated duplex lead wire with 24-gauge welded tip. With miniature plug. Not for liquid immersion.	0-370C	.3
108A TJ1/4-6	.64cm diameter x 15.2cm long stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	.5
108A TJ1/4-12	.64cm diameter x 30.5cm long stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	.5
108A TJ1/4-12TFE	.64cm diameter x 30.5cm long PTFE coated, stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	.5
108A TJ1/4-18	.64cm diameter x 45.7cm long stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	1.0
108A TJ1/4-18TFE	.64cm diameter x 45.7cm long PTFE coated, stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	1.0
108A TJ1/4-24	.64cm diameter x 61cm long stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	1.5
108A TJ1/4-24TFE	.64cm diameter x 61cm long PTFE coated, stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	1.5
108A TJ1/4-30	.64cm diameter x 76.2cm long stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	2.0
108A TJ1/8-12	.32cm diameter x 30.5cm long stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	.5
108A TJ1/8-12TFE	.32cm diameter x 30.5cm long PTFE coated, stainless-steel probe. With 183cm lead wire. With miniature plug. Type J.	0-750C	.5